



MINI-ROLL



PRODUCT PROFILE


Order Code	Lumen	Power	Voltage	Beam Angle	CCT	CRI
2383	2000lm	19W	100-240V	15°	3000K/4000K	Ra ≥ 80
2233	2000lm	19W	100-240V	24°	3000K/4000K	Ra ≥ 80
2234	2000lm	19W	100-240V	36°	3000K/4000K	Ra ≥ 80
2384	2500lm	25W	220-240V	15°	3000K/4000K	Ra ≥ 80
2313	2500lm	25W	220-240V	24°	3000K/4000K	Ra ≥ 80
2314	2500lm	25W	220-240V	36°	3000K/4000K	Ra ≥ 80

Optional Colors

- RAL9004 Black
- RAL9003 White
- RAL9006 Grey



Lighting Efficiency : ≥ 80%  
 Net Weight : 1.0kg  
 Installation : LED Track Spot Light  
 Material : Die-casting Aluminum & Plastic  
 PCS Per CTN : 8PCS



MIX-ROLL



PRODUCT PROFILE


Order Code	Lumen	Power	Voltage	Beam Angle	CCT	CRI
2761	2500lm	25W	220-240V	15°	3000K/4000K	Ra ≥ 80
2762	2500lm	25W	220-240V	24°	3000K/4000K	Ra ≥ 80
2763	2500lm	25W	220-240V	36°	3000K/4000K	Ra ≥ 80

Optional Colors

- RAL9004 Black
- RAL9003 White
- RAL9006 Grey



Available Accessories



Lighting Efficiency : ≥ 80%  
 Net Weight : 0.9kg  
 Installation : Recessed Mounting  
 Material : Die-casting Aluminum  
 PCS Per CTN : 12PCS

